

TORLYS Hardwood
SuperSolid 6 Series

PART 1 – MATERIALS

- .1 Prefinished hardwood flooring, consisting of a 4mm thick sawn hardwood top layer, a 11mm thick hardwood filleted core, and a 4mm thick sawn hardwood backing.
- .2 **TORLYS SuperSolid 6 Series** flooring shall be:
 - .1 *Size:* 5-7/8” wide (nominal) x Random Length, 24” to 75”;
average 56” (nominal)– 150mm wide x Random Length, 300mm to 1900mm; average 1425mm
 - .2 *Total Thickness:* 3/4” (nominal) – 19 mm
 - .3 *Type of Finishing:* Scratch-resistant Klumpp urethane
 - .4 *Edge Type:* Bevel 4-sides
 - .5 *Type of Decorative Top Layer:* Natural Wood
 - .6 *Type of Core:* Hardwood fillets
 - .7 *Type of Backing:* Natural Wood
 - .8 *Assembly System:* T&G
 - .9 *Colours:* As selected by the Architect
 - .10 *Type of Installation:* Nail-down; Glue-down; Floating
- .3 Accessories:
 - .1 TORLYS Hardwood Mouldings: As recommended by the manufacturer
 - .2 Colours: As selected by the architect

PART 2 – PACKAGING INFORMATION

- .1 *Square feet / Square metres per carton:* 21.47 sq. ft. / 1.995m²
- .2 *Weight per Carton:* 61.0 lbs / 27.7 kg

PART 3 – EXECUTION (Site Verification, Installation, Cleaning)

- 3.1 Site Verification and Installation
Contact TORLYS for specific installation instructions (nail-down, glue-down, or floating)
- 3.2 Cleaning
Clean the floor by sweeping or vacuuming; use TORLYS Floor Cleaner as needed.