

EVERWOODTM Vista

the ultimate flooring.



PROFESSIONAL



EASTON EW22004

TORLYS
smart floors

torlys.com

Beautiful. Durable. Waterproof.

No other luxury vinyl floor combines outstanding looks and high-traffic durability. Now you can have it all! Beautiful, precision-crafted luxury vinyl floors with stunning, on-trend planks that are waterproof, warm and quiet.

The Ultimate.
Engineering and design.

How It's Made.

- 1) **Top Layer**
 Ultra-thick 0.3mm (12 mils) wear layer for ultimate wear resistance
- 2) **Decorative Layer**
 Beautiful, authentic look and fade resistant
- 3) **TORLYS Ultra-Stable Smart Core**
 More than twice as thick as the industry standard
- 4) **TORLYS Uniclic® Joint**
 Gap-free installations and easy repairs** with TORLYS Bulldog Easy Plank Replacer™



The Ultimate.
TORLYS exclusives.



TORLYS BULLDOG™ Easy Plank Replacer
 “Your Floor’s Best Friend”

- The Bulldog™ allows you to:
- Fix major mishaps quickly and easily.
 - Replace a damaged plank, not your entire floor.**



Uniclic® joint technology – for remarkably stable, gap resistant floors.

Side and end joints have patented Uniclic joints, a system exclusively engineered for EverWood – the only floor backed by a gap warranty.



TORLYS Flood Warranty

EverWood & EverTile are protected from water damage caused by floods with TORLYS Flood Warranty.

***On floating installations.*



- | | | | | | | | | | |
|---------------------|-------------------|----------------------|-------------------------|-----------------------|---------------------------------|-------------------------|-----------------------|--------------------------|---------------------|
| | | | | | | | | | |
| Ultra-Stable | Waterproof | Gap Resistant | Warm & Quiet | Ease of Repair | Peace-of-Mind Durability | Easy to Maintain | Dent Resistant | Clean and Healthy | Pet Friendly |

EVERWOODTM

Vista



Great looks. Great value.

Affordable elegance that will accentuate any decor.

1/4" (T) x 4-7/8" (W) x 48-3/8" (L)
6.5mm (T) x 123mm (W) x 1230mm (L)

- Micro-bevels and low-gloss finish
- Softly textured, warm, comfortable and quiet underfoot
- 0.3mm (12mils) wear layer
- 4-sided finished bevels

**EverWood Vista does not include CorkPlusTM BLUE underlay.*



Warranties

5-Year Limited Commercial, Wear, Structural and Joint Integrity/No Gapping Warranty.

20-Year Homeowner Limited Warranty for Wear, Stain, and Water; and a Lifetime Structural and Joint Integrity/No Gapping Warranty.

EverWoodTM Vista is covered by an exclusive Flood Warranty. For details visit torlys.com.

SUTTER CREEK EW22000

PARK RIDGE EW22001

ASHFORD EW22002

CROOKED RIVER EW22003

EASTON EW22004

The Ultimate.
Finishing touches.



Flush Reducer

Made from the same top layer as your floor, this reducer is designed specifically for EverWood™ & EverTile™ and will install flush with the flooring.



Flush Stair Nosing

Made from the same top layer as your floor, the floor is clicked into the nosing for a flawless look, without transition bumps.



ThinStrip T-Moulding

A unique, extreme low profile transition moulding with a 1mm edge that is colour matched to the floor with a polyurethane coating for extra wear resistance. It is bendable for height variations between floors and uses a self-adhesive strip for easy installation.

Specially designed mouldings.

Design Flexibility...Clean Lines.

Imagine a floor with the embossed grain and tangible beauty of real hardwood. One that stands up to the demands of everyday use and can be installed with spectacular results in any space.

Hallways and Stairs

A style-matched, flush stair nosing creates a durable edge with clean lines.

From Room to Room

The reducer and stair nosing for EverWood are installed flush with the flooring, for a smooth and flawless look. Enjoy a seamless look from one room to another – no “speed bumps”*.

**Floors over 80 linear ft. may require expansion joints.*

ASTM and ANSI Product Performance Tests

| Standard | Description | Test Result | Notes |
|--|---|---|---|
| ASTM E648-14a | Critical Radiant Flux | Average Critical Radiant Flux: 0.72 W/cm ² | NFPA 101 Classification: Class 1 |
| ANSI A137.1-2012 (aka DCOF AcuTest) | Coefficient of Friction (Floor Slip Resistance) a) Dynamic Coefficient of Friction (wet) Coefficient of Friction (Floor Slip Resistance) b) Static Coefficient of Friction (dry) | Mean Result: 0.43 Mean Result: 0.80 | ANSI A137.1-2012 / DCOF AcuTest replaces ASTM C1028-07* |
| ASTM F970 | Static Load Limit / Residual Indentation @ 250 PSI Static Load Limit / Residual Indentation @ 1000 PSI | 0.003 inches 0.055 inches | |
| ASTM C518 | Thermal Resistance | SI Units 0.10 K·m ² /W | Imperial Units 0.59°F·ft ² ·h/BTU·in |
| ASTM F925-02 | Resistance to Chemicals | 0 = No Change | |
| ASTM F1515 | Resistance to Light | ΔE ≤ 8 | Test result after 300 hours exposure |
| CPSC-CH-C1001-09.3 (California Proposition 65) | Phthalates | Does not contain phthalate esters | |
| ASTM E492-09 / ASTM E989-06 | Impact Insulation Class | IIC 74 | Testing on 8" concrete slab, with suspended ceiling |
| ASTM E90-04 / ASTM E413-10 | Sound Transmission Coefficient | STC 66 | Testing on 8" concrete slab, with suspended ceiling |

*Note: "Obsolete, misleading test withdrawn by ASTM in 2014. Not valid for assessing pedestrian safety."
<http://www.astm.org/Standards/C1028.htm>

