

OLYMPIC COLLECTION

3/16" x 7" x 48" (nominal) | 5mm x 177.8mm x 1219.2mm

Paris Oak MQLL-550	Whistler Oak MQLL-551	Turin Oak MQLL-552	Tokyo Oak MQLL-553 High Shade Variation	
Sydney Oak MQLL-554 High Shade Variation	London Oak MQLL-555	Athens Oak MQLL-556	Rio Walnut MQLL-557 (All Over Texture) High Shade Variation	



torlys.com

OLYMPIC COLLECTION

Comfortable, quiet, waterproof and durable 5mm loose lay.

The Olympic collection is one of the very few EIR Loose Lay collections on the market, that is 100% Virgin Phthalate Free PVC.

- 100% Waterproof Multilayered Engineered Loose Lay with incapsulated stable fiberglass
- 0.5mm/20 mill wear layer
- Sound absorbent SafeGrip backer
- TORLYS Maxx Commercial Finish resists high traffic wear and staining and features built-in antimicrobial protection to keep floors cleaner between cleanings
- Precision bevel edges
- EIR textures^{*}
- Warm, comfortable and quiet underfoot
- Floorscore[®] Certified
- 100% Virgin PVC
- Anti-telegraphing performance for imperfect subfloors
- Recommended Underlayment: TORLYS VersaLay smooths out subfloor, offers acoustic comfort, eliminates the need for adhesives, and can be walked on immediately after installation

*Rio Walnut is not EIR

DIMENSIONS

Plank: 7" x 48" (nominal) 177.8mm x 1219.2mm

Thickness: 5mm / 3/16"

Wear Layer Thickness: 0.5mm / 20mil

18.67 sq. ft per carton

WARRANTY

Lifetime Limited Residential Warranty 15 Year Limited Commercial Warranty

TECHNICAL DATA		
Test	Test Method	Result
Flexibility	ASTM F137-08 (2013)	Pass
Resistance to Chemicals	ASTM F925-13	Pass
Resistance to Heat	ASTM F1514-03 (2013)	Pass
Effect of Castor Chair	NALFA LF 01-2011 Section 3.9	Pass
Dimensional Stability (after heat exposure)	ASTM F2199-09 (2014)	Pass
Static Load Limit	ASTM F970 (250 lb)	Residual Indentation 0.011mm
Critical Radiant Flux	ASTM E648/NFPA classification	Class 1
Coeffcient of Friction	ASTM D2047	Pass
Thermal Conductivity	ASTM C518-17	0.128W/(m.K)
Phthalate Content Test	CPSC-CH-C1001	Non detected





