

## PRODUCT FEATURES

### BEAUTY OF HARDWOOD

NatureTEK<sup>®</sup> offers the beauty of hardwood with innovative performance TEK<sup>®</sup>nology.

### ENHANCED SCRATCH PROTECTION

NatureTEK<sup>®</sup> provides up to four times more scratch protection than other products on the market.

### FADE RESISTANCE

NatureTEK<sup>®</sup> offers long-lasting brilliance that resists fading and preserves wood tones for years to come.

## PRODUCT SPECIFICATIONS

<b>Construction</b> .....	Laminated Wood
<b>Installation</b> .....	Uniclic <sup>®</sup>
<b>Thickness</b> .....	3/8"(nom. 25/64"); 8mm+2mm Attached Pad
<b>Plank Size</b> .....	7-1/2" W x 54-11/32" L
<b>Texture</b> .....	EIR
<b>AC Rating</b> .....	AC4
<b>Edge Profile</b> .....	GenuEdge <sup>®</sup>
<b>Sq. Ft. per Carton</b> .....	25.40
<b>Warranty</b> .....	Lifetime Surface & Subfloor Waterproof
	Limited Lifetime Residential
	5 YR Light to Medium Commercial

## ADDITIONAL BENEFITS

### LIFETIME WATERPROOF WARRANTY

WetProtect<sup>®</sup> TEK<sup>®</sup>nology provides a lifetime surface and subfloor waterproof warranty – for the right kind of waterproof.

### REALISTIC DESIGNS

GenuEdge<sup>®</sup> TEK<sup>®</sup>nology enables the surface design and color to ‘roll over’ the edge for the most realistic plank looks.

### CLEAN WITH STEAM OR WET MOP

Worry-free flooring that resists moisture damage – provides quick as well as the most effective cleaning.

### COMFORT UNDERFOOT

Featuring a 2mm attached pad that simplifies installation and reduces noise.



COLOR SHOWN: BURROW OAK | UP5881

PLEASE NOTE: INSTALLED FLOORING MAY VARY FROM PRINTED IMAGE OR SAMPLE.



**TAPIOCA OAK**  
UP5880




**BURROW OAK**  
UP5881



**TANNIN OAK**  
UP5882



**HUTIA OAK**  
UP5883



**GRIZZLY OAK**  
UP5884

## PERFORMANCE ACCESSORIES

INVENTORY STYLE NUMBER	COLOR NAME	5-IN-1	5-IN-1 BASE	OVERLAP STAIR NOSE	QUARTER ROUND	WATERPROOF QUARTER ROUND FOR WETPROTECT® FLOORS
39550	Tapioca Oak	DINC5-03285	DBASE-2	DMSNP-03285	DQND-03285	DWPQR-WHITE
39550	Burrow Oak	DINC5-06318	DBASE-2	DMSNP-06318	DQND-06318	DWPQR-WHITE
39550	Tannin Oak	DINC5-06319	DBASE-2	DMSNP-06319	DQND-06319	DWPQR-WHITE
39550	Hutia Oak	DINC5-06320	DBASE-2	DMSNP-06320	DQND-06320	DWPQR-WHITE
39550	Grizzly Oak	DINC5-05928	DBASE-2	DMSNP-05928	DQND-05928	DWPQR-WHITE

Performance Accessories offers color-coordinated transitions to give your floors a perfectly finished look.



**WATERPROOF QUARTER ROUND FOR WETPROTECT® FLOORS**  
These waterproof moldings cover the expansion space between the floor and wall and provide a water-tight seal.




**QUARTER ROUND**  
These pre-finished moldings cover the expansion space between the floor and the wall.



**OVERLAP STAIR NOSE**  
The overlap stair nose creates a transition to the edge of the step by overlapping the flooring on the back end instead of being flush.


The multifunctional 5-in-1 molding allows you to utilize a single transition to create five different applications.



**CARPET TRANSITION**  
The carpet transition provides a smooth transition between your hard surface floor and carpet.



**T-MOLDING**  
The T-molding is used to transition between flooring of equal heights and in doorways.



**END MOLDING**  
The end molding can be used to finish flooring where it meets vertical surfaces such as walls, fireplace hearths and sliding glass doors.



**HARD SURFACE REDUCER**  
The hard surface reducer connects two floors of different heights.



**STAIR NOSE\***  
The stair nose application provides a complete stair solution for both flush mount and overlap applications.

\*Stair nose assembly requires additional purchase of the aluminum track (BBASE).

Approved for use with the following TORLYS underlayments

- Safe and Sound 5-in-1
- TORLYS Cork Natural (2.5mm)
- TORLYS CorkPlus™ Blue (2.5mm)

note: the use of 6 mil poly vapour barrier is mandatory when using cork underlay or laminate with attached pad on cementitious subfloors.