

Noture TEKPLUS TILLETO | 39554

PRODUCT FEATURES

BEAUTY OF HARDWOOD

NatureTEK[®] offers the beauty of hardwood with innovative performance TEKnology.

ENHANCED SCRATCH PROTECTION

NatureTEK[®] provides up to four times more scratch protection than other products on the market.

FADE RESISTANCE

NatureTEK[®] offers long-lasting brilliance that resists fading and preserves wood tones for years to come.

WetProtect GenuEdge. UNICLIC C

PRODUCT SPECIFICATIONS

Construction	Laminated Wood
Installation	Uniclic®
Thickness1/2"(nom.15/32)	"); 10mm+2mm Attached Pad
Plank Size	
	EIR
AC Rating	AC4
Edge Profile	GenuEdge®
Sq. Ft. per Carton	
WarrantyLifetime Se	urface & Subfloor Waterproof
	Limited Lifetime Residential
5 YR	Light to Medium Commercial

ADDITIONAL BENEFITS

LIFETIME WATERPROOF WARRANTY

WetProtect^{*} TEKnology provides a lifetime surface and subfloor waterproof warranty – for the right kind of waterproof.

REALISTIC DESIGNS

GenuEdge^{*} TEKnology enables the surface design and color to 'roll over' the edge for the most realistic plank looks.

CLEAN WITH STEAM OR WET MOP

Worry-free flooring that resists moisture damage – provides quick as well as the most effective cleaning.

COMFORT UNDERFOOT

Featuring a 2mm attached pad that simplifies installation and reduces noise.





TILLETO



WOODLAND OAK UP3230



DUTCH OAK UP3231



GABLE OAK UP1858




HELEN OAK UP5889



TILLETO

PERFORMANCE



INVENTORY STYLE NUMBER	COLOR NAME	5-IN-1	5-IN-1 BASE	OVERLAP STAIR NOSE	QUARTER ROUND	WATERPROOF QUARTER ROUND FOR WETPROTECT® FLOORS
39554	Woodland Oak	DINC5-02791	DBASE-4	DMSNP-02791	DQND-02338	DWPQR-WHITE
39554	Dutch Oak	DINC5-05702	DBASE-4	DMSNP-05702	DQND-05702	DWPQR-WHITE
39554	Gable Oak	DINC5-03267	DBASE-4	DMSNP-03267	DQND-03267	DWPQR-WHITE
39554	Helen Oak	DINC5-06321	DBASE-4	DMSNP-06321	DQND-06321	DWPQR-WHITE

Performance Accessories offers color-coordinated transitions to give your floors a perfectly finished look.



WATERPROOF QUARTER ROUND FOR WETPROTECT* FLOORS These waterproof moldings cover the expansion space between the floor and wall and provide a water-tight seal.



QUARTER ROUND These pre-finished moldings cover the expansion space between the floor and the wall.



OVERLAP STAIR NOSE

The overlap stair nose creates a transition to the edge of the step by overlapping the flooring on the back end instead of being flush.

The multifunctional 5-in-1 molding allows you to utilize a single transition to create five different applications.



CARPET TRANSITION The carpet transition provides a smooth

transition between your hard surface floor and carpet.



HARD SURFACE REDUCER The hard surface reducer connects two floors of different heights.



T-MOLDING The T-molding is used to transition between flooring of equal heights and in doorways.



STAIR NOSE* The stair nose application provides a complete stair solution for both flush mount and overlap applications. "Stair nose assembly requires additional purchase of the aluminum track (BASE).



END MOLDING

The end molding can be used to finish flooring where it meets vertical surfaces such as walls, fireplace hearths and sliding glass doors.

Approved for use with the following TORLYS underlayments

- Safe and Sound 5-in-1
- TORLYS Cork Natural (2.5mm)
- TORLYS CorkPlus[™] Blue (2.5mm)

note: the use of 6 mil poly vapour barrier is mandatory when using cork underlay or laminate with attached pad on cementitious subfloors.