

# RigidWood™ Firm Vista

**TORLYS**  
smart floors



HELM OAK

 Water Proof

 Transition Free

 Antimicrobial

 Scratch Resistant

 Flood Warranty

 Easily Repairable

 Dent Resistant

 Gap Resistant

# RigidWood™ Firm Vista

5/32" (T) x 6" (W) x 47-3/4" (L) (nominal)  
4.5mm (T) x 150mm (W) x 1211.2mm (L)

23.47 SF per box  
54 boxes per pallet

## Details

- Beautiful, lightly textured surfaces with matching painted bevels.
- 0.3mm / 12 mil wear layer.
- Install directly over other hard surfaces with minimal subfloor preparation.
- Patented Uniclic® joint with pretension keeping any water on the surface of the floor.
- TORLYS Maxx Finish resists household wear and staining, and features built-in antimicrobial protection.
- TORLYS FoamPlus™ Blue attached underlay for superior sound reduction and shock-absorption with anti-crush technology. Infused with Microban® antimicrobial technology.
- Remarkable dimensional stability that can withstand temperature swings from -4 - 122°F (-20 - 50°C).
- More dent resistant than traditional LVT.
- Suitable to install over radiant heat.\*
- Conforms to subfloor for a quieter, more solid feel.
- Can be fixed/floated on the same floor.\*
- No peaking, gapping or cupping, guaranteed.\*

\*check installation instructions/warranty for details.

## The Smart Advantage SPC



### Waterproof

RigidWood™ is 100% waterproof - backed by TORLYS exclusive Flood Warranty.



### Transition Free

RigidWood™ is a remarkably stable floor that can be installed transition free in spaces up to 70' x 70'; no more "speed bumps" in doorways or long hallways.



### TORLYS Bulldog™ Easy Plank Replacer

TORLYS Bulldog™ enables single planks to be replaced, quickly and easily. No mess, no dust, no downtime.

SPINNAKER

RW-FMV151

BLUEPETER

RW-FMV153

HELM OAK

RW-FMV154

DECK OAK

RW-FMV152

FOREMAST

RW-FMV150



# A Cleaner Floor Starts Here.

Contribute to a cleaner home with built-in antimicrobial protection.



TORLYS Maxx Finish with built-in antimicrobial protection will keep your floors **99% cleaner** between cleanings, 24/7.

TORLYS FoamPlus™ Blue with Microban® offers safe and effective protection against the growth of mold and mildew under your floors.

For more information visit [torlys.com/CleanerFloors](http://torlys.com/CleanerFloors)



HELM OAK

## Finishing Touches

**TORLYS Multi-Purpose Moulding**  
Easy and convenient, the TORLYS multi-purpose moulding solution offers an adaptable and colour coordinated profile. Suitable for floating applications.\*

**TORLYS smartSTEP Moulding**  
A unique stair nosing solution to add the perfect finishing touch. TORLYS smartSTEP is made from a full piece of actual flooring, with the same Uniclic® joint as your floor for an easy and seamless installation.

*\*See installation instructions for details.*

## Sustainability

Every TORLYS Smart Floor has two lives. Years down the road when you want to change your floor, TORLYS will offer a 10% credit towards the purchase of a new floor when your existing TORLYS Smart Floor is donated to Habitat for Humanity.

## Warranty

**Lifetime Residential Limited Warranty\***

**5-Year Commercial Limited Warranty\***

RigidWood™ is covered by an exclusive **Flood Warranty**. Fully waterproof when installed with a perimeter seal.\*

*\*Visit [torlys.com](http://torlys.com) for full warranty and installation information.*

## Peace of Mind Assurance

Peace of Mind Assurance with TORLYS Satisfaction Guarantee - Love the style and colour of your floors or change them - no questions asked.\*


## Healthy Home - Indoor Air Quality

We follow some of the most stringent standards in the world. TORLYS flooring products meet California Section 01350 and/or FloorScore® certification.

## ASTM and ANSI Product Performance Tests

\*Visit [torlys.com](https://torlys.com) for details.

Standard	Description	Test Result	Notes
ASTM E648-17	Critical Radiant Flux	Average Critical Radiant Flux: $\geq 0.45 \text{ W/cm}^2$	NFPA Life Safety Code 101 Classification: Class 1
ASTM E662-17a	Smoke Density	$\leq 450$	Passes $\leq 450$ Criteria, as per NFPA Life Safety Code 101
Phthalates, as per CPSC-CH-C1001-09.3 (California Proposition 65)	Phthalates	Does not contain phthalate esters	
RoSH	Heavy Metals	Pass	
ASTM D5116-10 (Small Chamber)	Formaldehyde Emissions	No Formaldehyde	
ANSI A137.1-2012 (aka DCOF AcuTest)	Coefficient of Friction (Floor Slip Resistance): a) Dynamic Coefficient of Friction (wet) Coefficient of Friction (Floor Slip Resistance): b) Static Coefficient of Friction (dry)	Mean Result: 0.44  Mean Result: 0.49	Passes the $\geq 0.42$ requirement
ASTM F925	Resistance to Chemicals	Slight Surface Change / Dulling by White Mineral Oil and NaOH Solution	The scale is 0-3; 0 = no change; 1 = slight change; 2 = moderate change; 3 = severe change
ASTM F1515	Resistance to Light	$\Delta E \leq 8$	Test result after 400 hours exposure
ASTM E492-09 (2016) - ASTM E989-06 (2012)	Impact Insulation Class	IIC up to 73	Contact TORLYS for details
ASTM E90-09 (2016) / ASTM E413 - 16	Sound Transmission Coefficient	STC 61	



## Stable & Flexible Construction

1. TORLYS Maxx Finish (Antimicrobial | Anti-Wear)
2. Heavy Duty Wear Layer 0.3mm (12 mil) wear layer
3. Decorative Print Film
4. Rigid Core with Patented Uniclic® Joint
5. FoamPlus™ Blue Underlay with Microban®