

RigidWood™ Flex Elite

TORLYS
smart floors



ABBEY

-  Water Proof
-  Transition Free
-  Antimicrobial
-  Scratch Resistant
-  Flood Warranty
-  Easily Repairable
-  Dent Resistant
-  Gap Resistant

RigidWood™ Flex Elite

3/16" (T) x 7" (W) x 58-3/4" (L) (nominal)
5.5mm (T) x 178.1mm (W) x 1492mm (L)

22.88 SF per box
55 boxes per pallet

Details

- Beautiful, deep EIR textured surfaces with matching painted bevels.
- 0.55mm / 22 mil wear layer.
- Install directly over other hard surfaces with minimal subfloor preparation.
- Patented Uniclic® joint with pretension keeping any water on the surface of the floor.
- TORLYS Maxx Commercial Finish resists high traffic wear and staining, and features built-in antimicrobial protection.
- TORLYS FoamPlus™ Blue attached underlay for superior sound reduction and shock-absorption with anti-crush technology. Infused with Microban® antimicrobial technology.
- Remarkable dimensional stability that can withstand temperature swings from -4 - 122°F (-30 - 50°C).
- More dent resistant than traditional LVT.
- Suitable to install over radiant heat.*
- Conforms to subfloor for a quieter, more solid feel.
- Can be fixed/floated on the same floor.*
- No peaking, gapping or cupping, guaranteed.*

*check installation instructions/warranty for details.

The Smart Advantage SPC



Waterproof

RigidWood™ is 100% waterproof - backed by TORLYS exclusive Flood Warranty.



Transition Free

RigidWood™ is a remarkably stable floor that can be installed transition free in spaces up to 80' x 80'; no more "speed bumps" in doorways or long hallways.




TORLYS Bulldog™ Easy Plank Replacer

TORLYS Bulldog™ enables single planks to be replaced, quickly and easily. No mess, no dust, no downtime.



TRAFALGAR*

RW-FXE432



ABBEY

RW-FXE434




WICKHAM

RW-FXE431



STONINGTON*

RW-FXE430



BRONTE

RW-FXE433

*High shade variation



A Cleaner Floor Starts Here.

Contribute to a cleaner home with built-in antimicrobial protection.



TORLYS Maxx Commercial Finish with built-in antimicrobial protection will keep your floors **99% cleaner** between cleanings, **24/7**.

TORLYS FoamPlus™ Blue with Microban® offers safe and effective protection against the growth of mold and mildew under your floors.

For more information visit torlys.com/CleanerFloors



BRONTE



Finishing Touches

TORLYS Multi-Purpose Moulding
Easy and convenient, the TORLYS multi-purpose moulding solution offers an adaptable and colour coordinated profile. Suitable for floating applications.*

TORLYS smartSTEP Moulding
A unique stair nosing solution to add the perfect finishing touch. TORLYS smartSTEP is made from a full piece of actual flooring, with the same Uniclic® joint as your floor for an easy and seamless installation.

**See installation instructions for details.*

Sustainability

Every TORLYS Smart Floor has two lives. Years down the road when you want to change your floor, TORLYS will offer a 10% credit towards the purchase of a new floor when your existing TORLYS Smart Floor is donated to Habitat for Humanity.

Warranty

Lifetime Residential Limited Warranty*

15-Year Commercial Limited Warranty*

RigidWood™ is covered by an exclusive **Flood Warranty**. Fully waterproof when installed with a perimeter seal.*

**Visit torlys.com for full warranty and installation information.*

Peace of Mind Assurance

Peace of Mind Assurance with TORLYS Satisfaction Guarantee - Love the style and colour of your floors or change them - no questions asked.*


Healthy Home - Indoor Air Quality

We follow some of the most stringent standards in the world. TORLYS flooring products meet California Section 01350 and/or FloorScore® certification.

ASTM and ANSI Product Performance Tests

*Visit torlys.com for details.

Standard	Description	Test Result	Notes
ASTM E648-17	Critical Radiant Flux	Average Critical Radiant Flux: $\geq 0.45 \text{ W/cm}^2$	NFPA Life Safety Code 101 Classification: Class 1
ASTM E662-17a	Smoke Density	≤ 450	Passes ≤ 450 Criteria, as per NFPA Life Safety Code 101
Phthalates, as per CPSC-CH-C1001-09.3 (California Proposition 65)	Phthalates	Does not contain phthalate esters	
RoSH	Heavy Metals	Pass	
ASTM D5116-10 (Small Chamber)	Formaldehyde Emissions	No Formaldehyde	
ANSI A137.1-2012 (aka DCOF AcuTest)	Coefficient of Friction (Floor Slip Resistance): a) Dynamic Coefficient of Friction (wet) Coefficient of Friction (Floor Slip Resistance): b) Static Coefficient of Friction (dry)	Mean Result: 0.44 Mean Result: 0.49	Passes the ≥ 0.42 requirement
ASTM C518	Thermal Resistance (R value)	SI Units: $0.18 \text{ K}\cdot\text{m}^2/\text{W}$	Imperial Units: $1.04^\circ\text{F}\cdot\text{ft}^2\cdot\text{h}/\text{BTU}$
ASTM F925	Resistance to Chemicals	Slight Surface Change / Dulling by White Mineral Oil and NaOH Solution	The scale is 0-3; 0 = no change; 1 = slight change; 2 = moderate change; 3 = severe change
ASTM F1515	Resistance to Light	$\Delta E \leq 8$	Test result after 400 hours exposure
ASTM E492-09 (2016) - ASTM E989-06 (2012)	Impact Insulation Class	IIC 73	Contact TORLYS for details
ASTM E90-09 (2016) / ASTM E413 - 16	Sound Transmission Coefficient	STC 60	



Stable & Flexible Construction

1. TORLYS Maxx Commercial Finish (Antimicrobial | Anti-Wear)
2. Heavy Duty Wear Layer 0.55mm (22 mil) wear layer
3. Decorative Print Film
4. PVC Top Layer
5. Fibreglass
6. Rigid Core with Patented Uniclic® Joint
7. PVC Balance Layer
8. FoamPlus™ Blue Underlay with Microban®