



TORLYS XV

TORLYS XV value underlayment offers moisture and sound control with a self-sealing adhesive strip.

3/32" x 48" x 50' | 2.4mm x 1.22m x 15.24m



PRODUCT DETAILS

DIMENSIONS	3/32" x 48" x 50' (nominal) 2.4mm x 1.22m x 15.24m
ROLL/PALLET	200 sq. ft. (18.58m ²) 60 rolls per pallet
INSTALLATION	Above, On & Below Grade Radiant Heat Safe 
WARRANTY	10 Years

PRODUCT HIGHLIGHTS

- Value underlayment
- Built-in adhesive strip
- IIC 72*
- Moisture and sound control
- Available in full pallets only
- STC 62*

**Note: copy of IIC and STC reports are available upon request*

SUSTAINABILITY & INDOOR AIR QUALITY



ICC-ES E-1000 Series

RECOMMENDED APPLICATIONS

DESCRIPTION

LAMINATE WITHOUT ATTACHED UNDERLAY	Float	
LAMINATE WITH ATTACHED UNDERLAY	Float	
SMART HARDWOOD / CORK / LEATHER	Float	
SPC / WPC LUXURY VINYL	Float	
HARDWOOD	Glued	
HARDWOOD	Nailed	
LUXURY VINYL	Double Glue Down	
LUXURY VINYL	Direct Glue Down	

Only guaranteed for use with TORLYS floors detailed above